



**SPECIFICATION FOR THERMIC LANCE AND MINI LANCE PIPE****DAIWA THERMIC LANCE TYPE-W**

Norminal Size		Outside Diameter	Thickness (mm)	Weight (kg/m)	Sample of Section view
8A	1/4"	12.9	1.6	0.701	
		13.8	1.6	0.908	
14.2	14.2	14.2	2.0	1.00	
16.0	16.0	16.0	2.0	1.30	
10A	3/8"	17.3	2.3	1.52	
15A	1/2"	21.4	2.8	2.40	
		21.7	2.0	2.42	
20A	3/4"	27.2	2.8	3.72	




\* Other types and sizes may be available at customer's request.

**DAIWA THERMIC LANCE TYPE-T**


Norminal Size		Outside Diameter	Inner Diameter (mm)	Weight (kg/m)	Sample of Section view
8A	1/4"	12.9	2.8	0.794	
		13.8	2.8	0.903	
16.0	16.0	16.0	3.0	1.25	
10A	3/8"	17.3	4.5	1.47	
15A	1/2"	21.7	6.5	2.30	
		21.7	6.5	2.13	
20A	3/4"	26.5	6.5	3.33	
		27.2	6.0	3.63	

\* Other types and sizes may be available at customer's request.

**SPECIFICATIONS OF CONNECTION TYPE FOR THERMIC LANCE**

Specs	Description	Illustration
T/C	Both ends of pipe are threaded and attached with one screw socket and one plastic cap.	
PE	Both ends of pipe are plain, no threads, no swage.	
QC	Both ends of pipe are plain, one enlarged quick coupling is attached to one end for easy connection.	

**DAIWA MINI LANCE PIPE**

Norminal Size	Outside Diameter	Thickness (mm)	Weight (kg/m)	Section view
Φ6	6.0	1.1	0.133	
	6.0	1.6	0.174	
Φ7.5	7.5	1.6	0.2	
Φ8	8.0	1.1	0.187	
	8.0	1.6	0.252	
Φ9	9.0	1.1	0.214	
	9.0	1.6	0.292	
Φ10	9.8	1.1	0.236	